according to 1907/2006/EC, Article 31



Revision: 02.05.2023

Printing date 02.05.2023

Version number 14 (replaces version 13)

# SECTION 1: Identification of the substance/mixture and of the company/undertaking

- · 1.1 Product identifier
- · Trade name: 4CR 5400 Steinschlagschutz Spray
- 1.2 Relevant identified uses of the substance or mixture and uses advised against

No further relevant information available.

- · Application of the substance / the mixture Protective coating
- · 1.3 Details of the supplier of the safety data sheet
- · Manufacturer/Supplier:

4CR International GmbH & Co. KG

Donnerstrasse 10b 22763 Hamburg

Tel.: +49 (0) 40 69 60 99 30 E-Mail: Info@4CR.com

www.4CR.com

· 1.4 Emergency telephone number: +49(0)700 24112112 (CRM)

## SECTION 2: Hazards identification

- · 2.1 Classification of the substance or mixture
- · Classification according to Regulation (EC) No 1272/2008



H222-H229 Extremely flammable aerosol. Pressurised container: May burst if heated. Aerosol 1



environment

*Aquatic Chronic 2 H411* Toxic to aquatic life with long lasting effects.



| Skin Irrit. 2 | H315 | Causes skin irritation.            |
|---------------|------|------------------------------------|
| STOT SE 3     | H336 | May cause drowsiness or dizziness. |

May be fatal if swallowed and enters airways. Asp. Tox. 1 H304

- · 2.2 Label elements
- · Labelling according to Regulation (EC) No 1272/2008

The product is classified and labelled according to the GB CLP regulation.

· Hazard pictograms







GHS02

GHS07

- · Signal word Danger
- · Hazard-determining components of labelling:

Naphtha (petroleum), hydrotreated light

Hydrocarbons, C7, n-alkanes, isoalkanes, cyclics

cyclohexane

Methyl ethyl ketone

· Hazard statements

H222-H229 Extremely flammable aerosol. Pressurised container: May burst if heated.

(Contd. on page 2)

according to 1907/2006/EC, Article 31



Revision: 02.05.2023

Printing date 02.05.2023

Version number 14 (replaces version 13)

#### Trade name: 4CR 5400 Steinschlagschutz Spray

(Contd. of page 1) H315 Causes skin irritation. H336 May cause drowsiness or dizziness. H411 Toxic to aquatic life with long lasting effects. · Precautionary statements P101 If medical advice is needed, have product container or label at hand. P102 Keep out of reach of children. P103 Read carefully and follow all instructions. P210 Keep away from heat, hot surfaces, sparks, open flames and other ignition sources. No smoking. P211 Do not spray on an open flame or other ignition source. P251 Do not pierce or burn, even after use. P261 Avoid breathing dust/fume/gas/mist/vapours/spray. P410+P412 Protect from sunlight. Do not expose to temperatures exceeding 50 °C/122 °F. P501 Dispose of contents/container in accordance with local/regional/national/international regulations.

- · 2.3 Other hazards
- · Results of PBT and vPvB assessment
- · **PBT:** Not applicable.
- · vPvB: Not applicable.

#### SECTION 3: Composition/information on ingredients

- · 3.2 Mixtures
- · **Description:** Mixture of substances listed below with nonhazardous additions.

| · Dangerous components:  |   |          |
|--|---|----------|
| CAS: 115-10-6<br>EINECS: 204-065-8<br>Reg.nr.: 01-2119472128-37      | dimethyl ether  Flam. Gas 1A, H220; Press. Gas (Liq.), H280   | 25-50%   |
| CAS: 64742-49-0<br>EINECS: 265-151-9<br>Reg.nr.: 01-2119475514-35    | Naphtha (petroleum), hydrotreated light  The Flam. Liq. 2, H225; Asp. Tox. I, H304; Aquatic Chronic 2, H411; Skin Irrit. 2, H315; STOT SE 3, H336     | ≥10-<25% |
| EC number: 927-510-4<br>Reg.nr.: 01-2119475515-33                    | Hydrocarbons, C7, n-alkanes, isoalkanes, cyclics Flam. Liq. 2, H225; Asp. Tox. I, H304; Aquatic Chronic 2, H411; Skin Irrit. 2, H315; STOT SE 3, H336 | ≥10-<25% |
| CAS: 110-82-7<br>EINECS: 203-806-2<br>Reg.nr.: 01-2119463273-41      | cyclohexane  Flam. Liq. 2, H225; Asp. Tox. 1, H304; Aquatic Acute 1, H400; Aquatic Chronic 1, H410; Skin Irrit. 2, H315; STOT SE 3, H336              | 2.5-<10% |
| CAS: 78-93-3<br>EINECS: 201-159-0<br>Reg.nr.: 01-2119457290-43       | Methyl ethyl ketone  String Flam. Liq. 2, H225; String Eye Irrit. 2, H319; STOT SE 3, H336, EUH066  | 2.5-<10% |
| CAS: 141-78-6<br>EINECS: 205-500-4<br>Reg.nr.: 01-2119475103-46      | Ethyl acetate      Flam. Liq. 2, H225;    Eye Irrit. 2, H319; STOT SE 3, H336, EUH066   | 2.5-<10% |
| CAS: 64742-95-6<br>EC number: 918-668-5<br>Reg.nr.: 01-2119455851-35 | <i>Hydrocarbons, C9, aromatics ♦ Flam. Liq. 3, H226; ♦ Asp. Tox. 1, H304; ♦ Aquatic Chronic 2, H411; ♦ STOT SE 3, H335-H336, EUH066</i>               | 2.5-<5%  |

Additional information: For the wording of the listed hazard phrases refer to section 16.

## SECTION 4: First aid measures

- · 4.1 Description of first aid measures
- · General information: Immediately remove any clothing soiled by the product.

(Contd. on page 3)

according to 1907/2006/EC, Article 31



Revision: 02.05.2023

Printing date 02.05.2023

Version number 14 (replaces version 13)

Trade name: 4CR 5400 Steinschlagschutz Spray

(Contd. of page 2)

- · After inhalation: Supply fresh air; consult doctor in case of complaints.
- · After skin contact: Immediately rinse with water.
- · After eye contact: Rinse opened eye for several minutes under running water.
- · After swallowing: Seek immediate medical advice.
- 4.2 Most important symptoms and effects, both acute and delayed No further relevant information available.
- · 4.3 Indication of any immediate medical attention and special treatment needed

No further relevant information available.

#### SECTION 5: Firefighting measures

- · 5.1 Extinguishing media
- · Suitable extinguishing agents:

CO2, powder or water spray. Fight larger fires with water spray or alcohol resistant foam.

- 5.2 Special hazards arising from the substance or mixture No further relevant information available.
- · 5.3 Advice for firefighters
- · Protective equipment:

Wear self-contained respiratory protective device.

Do not inhale explosion gases or combustion gases.

#### SECTION 6: Accidental release measures

· 6.1 Personal precautions, protective equipment and emergency procedures

Wear protective equipment. Keep unprotected persons away.

· 6.2 Environmental precautions:

Do not allow product to reach sewage system or any water course.

Inform respective authorities in case of seepage into water course or sewage system.

Do not allow to enter sewers/surface or ground water.

· 6.3 Methods and material for containment and cleaning up:

Dispose contaminated material as waste according to section 13.

Ensure adequate ventilation.

· 6.4 Reference to other sections

See Section 7 for information on safe handling.

See Section 8 for information on personal protection equipment.

See Section 13 for disposal information.

## SECTION 7: Handling and storage

#### · 7.1 Precautions for safe handling

Keep away from heat and direct sunlight.

Ensure good ventilation/exhaustion at the workplace.

· Information about fire - and explosion protection:

Do not spray onto a naked flame or any incandescent material.

Keep ignition sources away - Do not smoke.

Pressurised container: protect from sunlight and do not expose to temperatures exceeding 50°C, i.e. electric lights. Do not pierce or burn, even after use.

- · 7.2 Conditions for safe storage, including any incompatibilities
- · Storage:
- Requirements to be met by storerooms and receptacles:

Observe official regulations on storing packagings with pressurised containers.

- Information about storage in one common storage facility: Store away from foodstuffs.
- · Further information about storage conditions:

Do not seal receptacle gas tight.

Keep container tightly sealed.

(Contd. on page 4)

according to 1907/2006/EC, Article 31



Revision: 02.05.2023

Printing date 02.05.2023

Version number 14 (replaces version 13)

Trade name: 4CR 5400 Steinschlagschutz Spray

(Contd. of page 3)

· Storage class: 2 B

· 7.3 Specific end use(s) No further relevant information available.

#### SECTION 8: Exposure controls/personal protection

# · 8.1 Control parameters

| · 8.1 Control parameters  |  |
|---|--|
| · Ingredients with limit values that require monitoring at the workplace: |  |
| 115-10-6 dimethyl ether   |  |
| WEL Short-term value: 958 mg/m³, 500 ppm                                  |  |
| Long-term value: 766 mg/m³, 400 ppm                                       |  |
| 110-82-7 cyclohexane  |  |
| WEL Short-term value: 1050 mg/m³, 300 ppm                                 |  |
| Long-term value: 350 mg/m³, 100 ppm                                       |  |
| 78-93-3 Methyl ethyl ketone   |  |
| WEL   Short-term value: 899 mg/m³, 300 ppm                                |  |
| Long-term value: 600 mg/m³, 200 ppm                                       |  |
| Sk, BMGV  |  |
| 141-78-6 Ethyl acetate  |  |
| WEL Short-term value: 1468 mg/m³, 400 ppm                                 |  |
| Long-term value: 734 mg/m³, 200 ppm                                       |  |
| · Ingredients with biological limit values:                               |  |
| 78-93-3 Methyl ethyl ketone   |  |
| BMGV   70 μmol/L  |  |
| Medium: urine   |  |
| Sampling time: post shift   |  |
| Parameter: butan-2-one  |  |

- · Additional information: The lists valid during the making were used as basis.
- · 8.2 Exposure controls
- · Appropriate engineering controls No further data; see section 7.
- · Individual protection measures, such as personal protective equipment
- · General protective and hygienic measures:

Keep away from foodstuffs, beverages and feed.

Immediately remove all soiled and contaminated clothing

Wash hands before breaks and at the end of work.

· Respiratory protection:



In case of brief exposure or low pollution use respiratory filter device. In case of intensive or longer exposure use self-contained respiratory protective device.

#### · Hand protection

Due to missing tests no recommendation to the glove material can be given for the product/ the preparation/ the chemical mixture.

Selection of the glove material on consideration of the penetration times, rates of diffusion and the degradation



Protective gloves (EN 374)

The glove material has to be impermeable and resistant to the product/ the substance/ the preparation.

· Material of gloves

The selection of the suitable gloves does not only depend on the material, but also on further marks of quality and varies from manufacturer to manufacturer. As the product is a preparation of several substances, the

(Contd. on page 5)

according to 1907/2006/EC, Article 31



Revision: 02.05.2023

Printing date 02.05.2023

Version number 14 (replaces version 13)

Trade name: 4CR 5400 Steinschlagschutz Spray

(Contd. of page 4)

resistance of the glove material can not be calculated in advance and has therefore to be checked prior to the application.

· Breakthrough time of glove material

The exact break trough time has to be found out by the manufacturer of the protective gloves and has to be observed.

· Eye/face protection Not required.

## SECTION 9: Physical and chemical properties

· 9.1 Information on basic physical and chemical properties

· General Information

· Physical state Aerosol

· Colour: According to product specification

· Odour: Characteristic · Odour threshold: Not determined. · Melting point/freezing point: Undetermined.

Boiling point or initial boiling point and boiling

range -24 °C

· Flammability Not applicable.

· Lower and upper explosion limit

· Lower: 0.8 Vol % · Upper: 18.6 Vol % · Flash point: 0 °C (DIN 53213) · Auto-ignition temperature: 235 °C (DIN 51794) Not determined. · Decomposition temperature: Not determined.  $\cdot pH$ 

· Viscosity:

· Kinematic viscosity Not determined. Dynamic: Not determined.

·Solubility

Not miscible or difficult to mix. · water:

· Partition coefficient n-octanol/water (log value) Not determined. · Vapour pressure at 20 °C: 5,200 hPa

· Density and/or relative density

· Density at 20 °C: 0.848 g/cm³ (DIN 53217)

· Relative density Not determined. · Vapour density Not determined.

· 9.2 Other information

· Appearance:

· Form: Aerosol

Important information on protection of health and environment, and on safety.

· Ignition temperature: Product is not selfigniting.

· Explosive properties: Product is not explosive. However, formation of

explosive air/vapour mixtures are possible.

· Solvent content:

· VOC (EC) 81.57% · Solids content (weight-%): 18.4 %

· Change in condition

· Evaporation rate Not applicable.

Information with regard to physical hazard classes

· Explosives Void · Flammable gases Void

(Contd. on page 6)

according to 1907/2006/EC, Article 31



Revision: 02.05.2023

Printing date 02.05.2023

Version number 14 (replaces version 13)

Trade name: 4CR 5400 Steinschlagschutz Spray

|  | (Contd. of page                                    |
|--|--|
| · Aerosols                                   | Extremely flammable aerosol. Pressurised container |
|  | May burst if heated.                               |
| · Oxidising gases                            | Void   |
| · Gases under pressure                       | Void   |
| · Flammable liquids                          | Void   |
| · Flammable solids                           | Void   |
| · Self-reactive substances and mixtures      | Void   |
| · Pyrophoric liquids                         | Void   |
| · Pyrophoric solids                          | Void   |
| · Self-heating substances and mixtures       | Void   |
| · Substances and mixtures, which emit flamma | ble  |
| gases in contact with water                  | Void   |
| · Oxidising liquids                          | Void   |
| · Oxidising solids                           | Void   |
| · Organic peroxides                          | Void   |
| · Corrosive to metals                        | Void   |
| Desensitised explosives                      | Void   |

#### SECTION 10: Stability and reactivity

- · 10.1 Reactivity No further relevant information available.
- · 10.2 Chemical stability
- Thermal decomposition / conditions to be avoided: No decomposition if used according to specifications.
- · 10.3 Possibility of hazardous reactions No dangerous reactions known.
- · 10.4 Conditions to avoid No further relevant information available.
- · 10.5 Incompatible materials: No further relevant information available.
- · 10.6 Hazardous decomposition products: Carbon monoxide

#### SECTION 11: Toxicological information

- · 11.1 Information on hazard classes as defined in Regulation (EC) No 1272/2008
- · Acute toxicity Based on available data, the classification criteria are not met.
- · Skin corrosion/irritation Causes skin irritation.
- · STOT-single exposure May cause drowsiness or dizziness.
- · Aspiration hazard May be fatal if swallowed and enters airways.
- · 11.2 Information on other hazards
- · Endocrine disrupting properties

78-93-3 Methyl ethyl ketone

List II

## SECTION 12: Ecological information

- · 12.1 Toxicity
- · Aquatic toxicity: No further relevant information available.
- · 12.2 Persistence and degradability No further relevant information available.
- · 12.3 Bioaccumulative potential No further relevant information available.
- · 12.4 Mobility in soil No further relevant information available.
- 12.5 Results of PBT and vPvB assessment
- · **PBT:** Not applicable.
- · vPvB: Not applicable.
- 12.6 Endocrine disrupting properties For information on endocrine disrupting properties see section 11.
- · 12.7 Other adverse effects
- · Remark: Toxic for fish

(Contd. on page 7)

# **Safety data sheet** according to 1907/2006/EC, Article 31



Revision: 02.05.2023

Printing date 02.05.2023

Version number 14 (replaces version 13)

Trade name: 4CR 5400 Steinschlagschutz Spray

(Contd. of page 6)

- · Additional ecological information:
- · General notes:

Water hazard class 2 (German Regulation): hazardous for water

Do not allow product to reach ground water, water course or sewage system.

Danger to drinking water if even small quantities leak into the ground.

Also poisonous for fish and plankton in water bodies.

Toxic for aquatic organisms

## SECTION 13: Disposal considerations

- · 13.1 Waste treatment methods
- · Recommendation

Must not be disposed together with household garbage. Do not allow product to reach sewage system.

- · Uncleaned packaging:
- · Recommendation: Disposal must be made according to official regulations.

| 14.1 UN number or ID number     | *******  |
|---------------------------------|--|
| ADR, IMDG, IATA                 | UN1950   |
| 14.2 UN proper shipping name    |  |
| ADR                             | UN1950 AEROSOLS, ENVIRONMENTALI                        |
| IMDG                            | HAZARDOUS<br>AEROSOLS (Naphtha, aliphatic, CYCLOHEXANE |
| INDG                            | MARINE POLLUTANT                                       |
| IATA                            | AEROSOLS, flammable                                    |
| 14.3 Transport hazard class(es) |  |
| ADR                             |  |
|                                 |  |
| Class                           | 2 5F Gases.  |
| Label                           | 2.1  |
| IMDG                            |  |
|                                 |  |
| Class                           | 2.1 Gases.   |
| Label                           | 2.1  |
| IATA                            |  |
|                                 |  |
| Class                           | 2.1 Gases.   |
| Lahel                           | 2.1  |

# **Safety data sheet** according to 1907/2006/EC, Article 31



Revision: 02.05.2023

Printing date 02.05.2023

Version number 14 (replaces version 13)

Trade name: 4CR 5400 Steinschlagschutz Spray

|   | (Contd. of page  |
|---|--|
| 14.4 Packing group<br>ADR, IMDG, IATA   | Void   |
| · 14.5 Environmental hazards:   | Product contains environmentally hazardous substances cyclohexane, Naphtha, aliphatic  |
| Marine pollutant:   | Yes<br>Symbol (fish and tree)  |
| Special marking (ADR):  | Symbol (fish and tree)   |
| 14.6 Special precautions for user<br>Hazard identification number (Kemler code):<br>EMS Number: | Warning: Gases.<br>-<br>F-D,S-U  |
| Stowage Code  | SW1 Protected from sources of heat.<br>SW22 For AEROSOLS with a maximum capacity of<br>litre: Category A. For AEROSOLS with a capacity abov<br>1 litre: Category B. For WASTE AEROSOLS: Categor<br>C, Clear of living quarters.                                |
| Segregation Code  | SG69 For AEROSOLS with a maximum capacity of litre: Segregation as for class 9. Stow "separated from" class except for division 1.4. For AEROSOLS with a capacity above 1 litre: Segregation as for the appropriate subdivision of class 2 For WASTE AEROSOLS: |
|   | Segregation as for the appropriate subdivision of class 2  |
| 14.7 Maritime transport in bulk according to IM instruments                                     | Not applicable.  |
| Transport/Additional information:   |  |
| ADR Limited quantities (LQ) Transport category Tunnel restriction code                          | 1L<br>2<br>D   |
| IMDG<br>Limited quantities (LQ)   | 1L   |
| UN "Model Regulation":  | UN 1950 AEROSOLS, 2.1, ENVIRONMENTALL<br>HAZARDOUS   |

# SECTION 15: Regulatory information

- 15.1 Safety, health and environmental regulations/legislation specific for the substance or mixture
- · Directive 2012/18/EU
- · Named dangerous substances ANNEX I None of the ingredients is listed.
- · Seveso category

P3a FLAMMABLE AEROSOLS

E2 Hazardous to the Aquatic Environment

- · Qualifying quantity (tonnes) for the application of lower-tier requirements 150 t
- · Qualifying quantity (tonnes) for the application of upper-tier requirements 500 t
- · National regulations:
- · Additional classification according to Decree on Hazardous Materials, Annex II:

| Class | Share in % |
|-------|------------|
| NK    | 50-100     |

(Contd. on page 9)

according to 1907/2006/EC, Article 31



Revision: 02.05.2023

Printing date 02.05.2023

Version number 14 (replaces version 13)

Trade name: 4CR 5400 Steinschlagschutz Spray

(Contd. of page 8)

• 15.2 Chemical safety assessment: A Chemical Safety Assessment has not been carried out.

## SECTION 16: Other information

This information is based on our present knowledge. However, this shall not constitute a guarantee for any specific product features and shall not establish a legally valid contractual relationship.

#### Relevant phrases

- H220 Extremely flammable gas.
- H225 Highly flammable liquid and vapour.
- H226 Flammable liquid and vapour.
- H280 Contains gas under pressure; may explode if heated.
- H304 May be fatal if swallowed and enters airways.
- H315 Causes skin irritation.
- H319 Causes serious eye irritation.
- H335 May cause respiratory irritation.
- H336 May cause drowsiness or dizziness.
- H400 Very toxic to aquatic life.
- H410 Very toxic to aquatic life with long lasting effects.
- H411 Toxic to aquatic life with long lasting effects.

EUH066 Repeated exposure may cause skin dryness or cracking.

#### · Classification according to Regulation (EC) No 1272/2008

The classification of the mixture is generally based on the calculation method using substance data according to Regulation (EC) No 1272/2008.

#### · Abbreviations and acronyms:

RID: Règlement international concernant le transport des marchandises dangereuses par chemin de fer (Regulations Concerning the International Transport of Dangerous Goods by Rail)

IATA-DGR: Dangerous Goods Regulations by the "International Air Transport Association" (IATA)

ICAO: International Civil Aviation Organisation

ICAO-TI: Technical Instructions by the "International Civil Aviation Organisation" (ICAO)

ADR: Accord relatif au transport international des marchandises dangereuses par route (European Agreement Concerning the International Carriage of Dangerous Goods by Road)

IMDG: International Maritime Code for Dangerous Goods

IATA: International Air Transport Association

GHS: Globally Harmonised System of Classification and Labelling of Chemicals

EINECS: European Inventory of Existing Commercial Chemical Substances

ELINCS: European List of Notified Chemical Substances

CAS: Chemical Abstracts Service (division of the American Chemical Society) VOC: Volatile Organic Compounds (USA, EU)

PBT: Persistent, Bioaccumulative and Toxic

vPvB: very Persistent and very Bioaccumulative

Flam. Gas 1A: Flammable gases - Category 1A

Aerosol 1: Aerosols - Category 1

Press. Gas (Liq.): Gases under pressure - Liquefied gas

Flam. Liq. 2: Flammable liquids - Category 2

Flam. Liq. 3: Flammable liquids - Category 3

Skin Irrit. 2: Skin corrosion/irritation – Category 2

Eye Irrit. 2: Serious eye damage/eye irritation – Category 2

STOT SE 3: Specific target organ toxicity (single exposure) – Category 3

Asp. Tox. 1: Aspiration hazard - Category 1

Aquatic Acute 1: Hazardous to the aquatic environment - acute aquatic hazard - Category 1

Aquatic Chronic 1: Hazardous to the aquatic environment - long-term aquatic hazard - Category I

Aquatic Chronic 2: Hazardous to the aquatic environment - long-term aquatic hazard - Category 2

\* Data compared to the previous version altered.