



Art.-No.:6.5400.0501
6.5400.0502

5400

Stone Chip Protection Spray

Characteristics

4CR Stone Chip Protection Spray 5400 is an overcoatable, durable elastic, protection against stone chips, corrosion, de-icing salt and mechanical wear. Also suitable as anti-noise compound, sealing film and underbody protection. Reliable long-term protection for spoilers, skirting and doors.

Tech Tip

- fast srying
- durable elasticity
- does not drip or run
- abrasion resistant
- excellent anti-noise characteristics
- once fully cured, recoatable with all customary painting systems

Application

Substrate: The substrate must be clean from rust, grease, polishing agents and sanded. If necessary primed.

Pretreatment/Cleansing: Pre-cleansing with 4CR silicone remover.

Processing conditions: From +10°C and uo to 80% relative air humidity.

All substrates must be clean, dry and free from grease. Shake can vigorously for approx. 2 mins. prio to use. Spraying distance approx. 20-30 cm. Apply layers evenly approx. 300 - 450 µm. After use, turn can upside down and spray until the valve is clean, this prevents the valve from clogging up.

Technical Data

Dust-dry	after approx. 20 mins.
Content	500 ml
Overcoatable	after approx. 8 h
Colour	grey (6.5400.0501) / black (6.5400.0502)

Storage and Transportation

The product may not be stored under +10°C and above +30°C the packaging must be protected from direct sunlight and heat.

Cool and moisture free stored the product is tenable for a minimum of 2 years in the unopened original packaging.