Technical Data Sheet Revised:2016-05-10 | 1/1



Art.-No.: 6.1180.2514

1180

Striping Tape

Characteristics

Pre-cut flexible fine line tape designed for making striping cars a simple job allowing multitude of patterns.

Replicates Coach Lines Multi-configuration Eight Pullouts Lay Flat No Bleed 8 stripes x 1.5mm

Tech Tip

The product is pre-cut into 8 sections across the roll making it ideal for striping coach lines in a multitude of configurations.

Application

- 1. Choose the area to be striped.
- 2. Apply the tape on to the vehicle applying light pressure.
- 3. Select the desired stripe configuration and pull out the desired sections. Once this is done press the tape firmly down along its length.
- 4. Mask up the rest of the area.
- 5. Spray with the desired colour.
- 6. Once dry remove the tape leaving your newly painted stripes.

Technical Data

Carrier Embossed Polypropylene

 $\begin{array}{lll} \mbox{Colour} & \mbox{Olive green} \\ \mbox{Width} & 25\mbox{mm} \ (+/\mbox{-} 1\mbox{mm}) \\ \mbox{Length} & 14\mbox{m} \ (+/\mbox{-} 0.1\mbox{m}) \\ \mbox{Thickness} & 0.127\mbox{mm} \mbox{PSTC-33} \\ \end{array}$

Adhesive Pigmented Urethane Pressure Sensitive Adhesive

Tensile Strength 0.215 kg/mm ASTM D-3759

Elongation at Break 600%

Adhesion to Steel 33.6 g/mm ASTM D-3330 Heat Resistance 138°C Maximum for 45 minutes

Storage and Transportation

One year from date of receipt by customer when stored at 22°C (72°F) and 50% relative humidity.

