Accr *Revision: 27.04.2023*

Printing date 27.04.2023

Version number 15 (replaces version 14)

SECTION 1: Identification of the substance/mixture and of the company/undertaking

· 1.1 Product identifier

· Trade name: 4CR 2030 Kunststoffspachtel

1.2 Relevant identified uses of the substance or mixture and uses advised against

No further relevant information available. • Application of the substance / the mixture Knife filler/Surfacer

• 1.3 Details of the supplier of the safety data sheet • Manufacturer/Supplier: 4CR International GmbH & Co. KG Donnerstrasse 10b 22763 Hamburg Tel.: +49 (0) 40 69 60 99 30 E-Mail: Info@4CR.com www.4CR.com

• 1.4 Emergency telephone number: +49(0)700 24112112 (CRM)

SECTION 2: Hazards identification

· 2.1 Classification of the substance or mixture · Classification according to Regulation (EC) No 1272/2008

flame

Flam. Liq. 3 H226 Flammable liquid and vapour.



Repr. 2H361d Suspected of damaging the unborn child.STOT RE 1H372Causes damage to the hearing organs through prolonged or repeated exposure.



Skin Irrit. 2H315Causes skin irritation.Eye Irrit. 2H319Causes serious eye irritation.Skin Sens. 1H317May cause an allergic skin reaction.

2.2 Label elements
 Labelling according to Regulation (EC) No 1272/2008
 The product is classified and labelled according to the GB CLP regulation.
 Hazard pictograms



· Signal word Danger

• Hazard-determining components of labelling: Styrene maleic anhydride 2,2'-(m-Tolylimino)diethanol Reaction mass of 2,2'-[(4-methylphenyl)imino]bisethanol and Ethanol 2-[[2-(2-hydroxyethoxy)ethyl](4methylphenyl)amino]-

(Contd. on page 2)

GB

according to 1907/2006/EC, Article 31 Version number 15 (replaces version 14)



Printing date 27.04.2023

Trade name: 4CR 2030 Kunststoffspachtel

	(Contd. of page 1)
· Hazard statement	'S
H226 Flammable	e liquid and vapour.
H315 Causes ski	n irritation.
H319 Causes ser	ious eye irritation.
H317 May cause	an allergic skin reaction.
H361d Suspected	of damaging the unborn child.
	mage to the hearing organs through prolonged or repeated exposure.
· Precautionary sta	
P210	Keep away from heat, hot surfaces, sparks, open flames and other ignition sources. No
	smoking.
P260	Do not breathe dust/fume/gas/mist/vapours/spray.
P280	Wear protective gloves/protective clothing/eye protection/face protection/hearing
	protection.
P303+P361+P35	3 IF ON SKIN (or hair): Take off immediately all contaminated clothing. Rinse skin with
	water [or shower].
P305+P351+P33	8 IF IN EYES: Rinse cautiously with water for several minutes. Remove contact lenses, if
	present and easy to do. Continue rinsing.
P403+P235	
$\cdot 2.3$ Other hazards	1 1
	nd vPvB assessment
	11 11 11 USSESSMEN

· **PBT:** Not applicable.

• **vPvB:** Not applicable.

*

Г

SECTION 3: Composition/information on ingredients

· 3.2 Mixtures

• Description: Mixture of substances listed below with nonhazardous additions.

· Dangerous components:

CAS: 100-42-5	Styrene	≥10-<15%
EINECS: 202-851-5 Reg.nr.: 01-2119457861-32	Flam. Liq. 3, H226; Repr. 2, H361d; STOT RE 1, H372; Asp. Tox. 1, H304; Acute Tox. 4, H332; Skin Irrit. 2, H315; Eye Irrit. 2, H319; STOT SE 3, H335; Aquatic Chronic 3, H412	
CAS: 91-99-6 EINECS: 202-114-8	2,2'-(m-Tolylimino)diethanol STOT RE 2, H373; O Eye Dam. 1, H318; Acute Tox. 4, H302; Skin Irrit. 2, H315; Skin Sens. 1B, H317	<i>≥</i> 0.1-<1%
EC number: 911-490-9	Reaction mass of 2,2'-[(4-methylphenyl)imino]bisethanol and Ethanol 2-[[2-(2-hydroxyethoxy)ethyl](4-methylphenyl) amino]- Eye Dam. 1, H318; Acute Tox. 4, H302; Skin Irrit. 2, H315; Skin Sens. 1, H317; Aquatic Chronic 3, H412	<i>≥</i> 0.1-<1%
CAS: 108-31-6 EINECS: 203-571-6 Reg.nr.: 01-2119472428-31	maleic anhydride Resp. Sens. 1, H334; STOT RE 1, H372; Skin Corr. 1B, H314; Eye Dam. 1, H318; Acute Tox. 4, H302; Skin Sens. 1A, H317, EUH071 Specific concentration limit: Skin Sens. 1A; H317: $C \ge 0.001$ %	≥0.001-<0.1%

• Additional information: For the wording of the listed hazard phrases refer to section 16.

SECTION 4: First aid measures

• 4.1 Description of first aid measures

• General information: Immediately remove any clothing soiled by the product.

(Contd. on page 3)

GB

according to 1907/2006/EC, Article 31



Printing date 27.04.2023

Version number 15 (replaces version 14)

Trade name: 4CR 2030 Kunststoffspachtel

(Contd. of page 2)

• After inhalation:

- Supply fresh air and to be sure call for a doctor.
- In case of unconsciousness place patient stably in side position for transportation.
- *After skin contact: Immediately rinse with water.*

• After eye contact:

- Rinse opened eye for several minutes under running water. If symptoms persist, consult a doctor.
- · After swallowing: If symptoms persist consult doctor.
- 4.2 Most important symptoms and effects, both acute and delayed No further relevant information available.
- 4.3 Indication of any immediate medical attention and special treatment needed
- No further relevant information available.

SECTION 5: Firefighting measures

- 5.1 Extinguishing media
- · Suitable extinguishing agents:
- CO2, powder or water spray. Fight larger fires with water spray or alcohol resistant foam.
- For safety reasons unsuitable extinguishing agents: Water with full jet
- 5.2 Special hazards arising from the substance or mixture
- During heating or in case of fire poisonous gases are produced.
- 5.3 Advice for firefighters
- Protective equipment: Mouth respiratory protective device.

SECTION 6: Accidental release measures

• 6.1 Personal precautions, protective equipment and emergency procedures

Mount respiratory protective device.

- Wear protective equipment. Keep unprotected persons away.
- 6.2 Environmental precautions: Do not allow to enter sewers/ surface or ground water.
- \cdot 6.3 Methods and material for containment and cleaning up:
- Absorb with liquid-binding material (sand, diatomite, acid binders, universal binders, sawdust). Dispose contaminated material as waste according to section 13. Ensure adequate ventilation.
- 6.4 Reference to other sections
- See Section 7 for information on safe handling.
- See Section 8 for information on personal protection equipment.

See Section 13 for disposal information.

SECTION 7: Handling and storage

· 7.1 Precautions for safe handling

- Ensure good ventilation/exhaustion at the workplace. Open and handle receptacle with care. Prevent formation of aerosols. • Information about fire - and explosion protection:
- Keep ignition sources away Do not smoke. Protect against electrostatic charges.
- Keep respiratory protective device available.
- · 7.2 Conditions for safe storage, including any incompatibilities

• Storage:

- Requirements to be met by storerooms and receptacles: No special requirements.
- Information about storage in one common storage facility: Store away from foodstuffs.
- Further information about storage conditions: Keep container tightly sealed.

• Storage class: 3

(Contd. on page 4)

according to 1907/2006/EC, Article 31



Printing date 27.04.2023

Version number 15 (replaces version 14)

Trade name: 4CR 2030 Kunststoffspachtel

• 7.3 Specific end use(s) No further relevant information available.

(Contd. of page 3)

SECTION 8: Exposure controls/personal protection

· 8.1 Control parameters

Ingredients with limit values that require monitoring at the workplace:

100-42-5 Styrene

WEL Short-term value: 1080 mg/m³, 250 ppm Long-term value: 430 mg/m³, 100 ppm

108-31-6 maleic anhydride

WEL Short-term value: 3 mg/m³

Long-term value: 1 mg/m³

Sen

· Additional information: The lists valid during the making were used as basis.

· 8.2 Exposure controls

- Appropriate engineering controls No further data; see section 7.
- · Individual protection measures, such as personal protective equipment
- General protective and hygienic measures:

Keep away from foodstuffs, beverages and feed.

Immediately remove all soiled and contaminated clothing

Wash hands before breaks and at the end of work.

Store protective clothing separately.

Avoid contact with the eyes.

Avoid contact with the eyes and skin.

• Respiratory protection:



In case of brief exposure or low pollution use respiratory filter device. In case of intensive or longer exposure use self-contained respiratory protective device.

· Hand protection

Due to missing tests no recommendation to the glove material can be given for the product/ the preparation/ the chemical mixture.

Selection of the glove material on consideration of the penetration times, rates of diffusion and the degradation



Protective gloves (EN 374)

The glove material has to be impermeable and resistant to the product/ the substance/ the preparation.

· Material of gloves

The selection of the suitable gloves does not only depend on the material, but also on further marks of quality and varies from manufacturer to manufacturer. As the product is a preparation of several substances, the resistance of the glove material can not be calculated in advance and has therefore to be checked prior to the application.


Breakthrough time of glove material

The exact break trough time has to be found out by the manufacturer of the protective gloves and has to be observed.

(Contd. on page 5)

GB


according to 1907/2006/EC, Article 31



Version number 15 (replaces version 14)



Trade name: 4CR 2030 Kunststoffspachtel



- GB

according to 1907/2006/EC, Article 31



Printing date 27.04.2023

Version number 15 (replaces version 14)

Trade name: 4CR 2030 Kunststoffspachtel

		(Contd. of page 5
Oxidising gases	Void	
Gases under pressure	Void	
Flammable liquids	Flammable liquid and vapour.	
Flammable solids	Void	
Self-reactive substances and mixtures	Void	
Pyrophoric liquids	Void	
Pyrophoric solids	Void	
Self-heating substances and mixtures	Void	
Substances and mixtures, which emit flammable	e	
gases in contact with water	Void	
Oxidising liquids	Void	
Oxidising solids	Void	
Organic peroxides	Void	
Corrosive to metals	Void	
Desensitised explosives	Void	

SECTION 10: Stability and reactivity

· 10.1 Reactivity No further relevant information available.

- · 10.2 Chemical stability
- Thermal decomposition / conditions to be avoided: No decomposition if used according to specifications.
- 10.3 Possibility of hazardous reactions No dangerous reactions known.
- \cdot 10.4 Conditions to avoid No further relevant information available.
- 10.5 Incompatible materials: No further relevant information available.
- 10.6 Hazardous decomposition products: Carbon monoxide

SECTION 11: Toxicological information

· 11.1 Information on hazard classes as defined in Regulation (EC) No 1272/2008

- Acute toxicity Based on available data, the classification criteria are not met.
- · Skin corrosion/irritation Causes skin irritation.
- · Serious eye damage/irritation Causes serious eye irritation.
- *Respiratory or skin sensitisation* May cause an allergic skin reaction.
- *Reproductive toxicity Suspected of damaging the unborn child.*
- STOT-repeated exposure Causes damage to the hearing organs through prolonged or repeated exposure.

SECTION 12: Ecological information

- · 12.1 Toxicity
- Aquatic toxicity: No further relevant information available.
- 12.2 Persistence and degradability No further relevant information available.
- 12.3 Bioaccumulative potential No further relevant information available.
- · 12.4 Mobility in soil No further relevant information available.
- 12.5 Results of PBT and vPvB assessment
- *PBT:* Not applicable.
- **vPvB:** Not applicable.
- 12.6 Endocrine disrupting properties For information on endocrine disrupting properties see section 11.
- · 12.7 Other adverse effects
- · Additional ecological information:
- · General notes:
- Water hazard class 2 (German Regulation) : hazardous for water

Do not allow product to reach ground water, water course or sewage system.

(Contd. on page 7)

GB

ECR *Revision: 27.04.2023*

Printing date 27.04.2023

Version number 15 (replaces version 14)

Trade name: 4CR 2030 Kunststoffspachtel

Danger to drinking water if even small quantities leak into the ground.

(Contd. of page 6)

SECTION 13: Disposal considerations

· 13.1 Waste treatment methods

· Recommendation

Must not be disposed together with household garbage. Do not allow product to reach sewage system.

· Uncleaned packaging:

• *Recommendation: Disposal must be made according to official regulations.*

SECTION 14: Transport information	
14.1 UN number or ID number ADR, IMDG, IATA	UN3269
· 14.2 UN proper shipping name · ADR · IMDG, IATA	UN3269 POLYESTER RESIN KIT POLYESTER RESIN KIT
14.3 Transport hazard class(es)	
ADR	
· Class · Label	3 (F3) Flammable liquids.
· IMDG, IATA	
· Class · Label	3 Flammable liquids. 3
· 14.4 Packing group	
· ADR, IMDG, IATA	111
14.5 Environmental hazards: Marine pollutant:	No
14.6 Special precautions for user	Warning: Flammable liquids.
 Hazard identification number (Kemler code): EMS Number: Stowage Category 	- F-E, <u>S-D</u> A
· 14.7 Maritime transport in bulk according to IM instruments	<i>IO</i> Not applicable.
• Transport/Additional information:	
· ADR · Limited quantities (LQ)	5L
• Transport category • Tunnel restriction code	3 E

A Revision: 27.04.2023

Printing date 27.04.2023

Version number 15 (replaces version 14)

Trade name: 4CR 2030 Kunststoffspachtel

(Contd. of page 7)

 • IMDG

 • Limited quantities (LQ)

 5L

 • UN "Model Regulation":

 UN 3269 POLYESTER RESIN KIT, 3, III

SECTION 15: Regulatory information

· 15.1 Safety, health and environmental regulations/legislation specific for the substance or mixture

· Directive 2012/18/EU

· Named dangerous substances - ANNEX I None of the ingredients is listed.

· Seveso category P5c FLAMMABLE LIQUIDS

• Qualifying quantity (tonnes) for the application of lower-tier requirements 5,000 t

• Qualifying quantity (tonnes) for the application of upper-tier requirements 50,000 t

· National regulations:

• Additional classification according to Decree on Hazardous Materials, Annex II:

Class Share in %

NK 10-25

• 15.2 Chemical safety assessment: A Chemical Safety Assessment has not been carried out.

SECTION 16: Other information

This information is based on our present knowledge. However, this shall not constitute a guarantee for any specific product features and shall not establish a legally valid contractual relationship.

· Relevant phrases

- H226 Flammable liquid and vapour.
- H302 Harmful if swallowed.
- H304 May be fatal if swallowed and enters airways.
- H314 Causes severe skin burns and eye damage.
- H315 Causes skin irritation.
- H317 May cause an allergic skin reaction.
- H318 Causes serious eye damage.
- H319 Causes serious eye irritation.
- H332 Harmful if inhaled.
- H334 May cause allergy or asthma symptoms or breathing difficulties if inhaled.
- H335 May cause respiratory irritation.
- H361d Suspected of damaging the unborn child.
- H372 Causes damage to organs through prolonged or repeated exposure.
- H373 May cause damage to organs through prolonged or repeated exposure.
- H412 Harmful to aquatic life with long lasting effects.
- EUH071 Corrosive to the respiratory tract.

· Classification according to Regulation (EC) No 1272/2008

The classification of the mixture is generally based on the calculation method using substance data according to Regulation (EC) No 1272/2008.

· Abbreviations and acronyms:

RID: Règlement international concernant le transport des marchandises dangereuses par chemin de fer (Regulations Concerning the International Transport of Dangerous Goods by Rail)

- ICAO: International Civil Aviation Organisation
- ADR: Accord relatif au transport international des marchandises dangereuses par route (European Agreement Concerning the International Carriage of Dangerous Goods by Road)
- IMDG: International Maritime Code for Dangerous Goods
- IATA: International Air Transport Association
- GHS: Globally Harmonised System of Classification and Labelling of Chemicals

EINECS: European Inventory of Existing Commercial Chemical Substances

ELINCS: European List of Notified Chemical Substances

(Contd. on page 9)



Printing date 27.04.2023

Version number 15 (replaces version 14)

Trade name: 4CR 2030 Kunststoffspachtel

	(Contd. of page 8)
CAS: Chemical Abstracts Service (division of the American Chemical Society)	(201101 01 1080 0)
VOC: Volatile Organic Compounds (USA, EU)	
PBT: Persistent. Bioaccumulative and Toxic	
vPvB: very Persistent and very Bioaccumulative	
Flam. Liq. 3: Flammable liquids – Category 3	
Acute Tox, 4: Acute toxicity – Category 4	
Skin Corr. 1B: Skin corrosion/irritation – Category 1B	
Skin Irrit. 2: Skin corrosion/irritation – Category 2	
Eye Dam. 1: Serious eve damage/eye irritation – Category 1	
Eye Irrit. 2: Serious eye damage/eye irritation – Category 2	
Resp. Sens. 1: Respiratory sensitisation – Category 1	
Skin Sens. 1: Skin sensitisation – Category 1	
Skin Sens. 1A: Skin sensitisation – Category 1A	
Skin Sens. 1B: Skin sensitisation – Category 1B	
Repr. 2: Reproductive toxicity – Category 2	
STOT SE 3: Specific target organ toxicity (single exposure) – Category 3	
STOT RE 1: Specific target organ toxicity (repeated exposure) – Category 1	
STOT RE 2: Specific target organ toxicity (repeated exposure) – Category 2	
Asp. Tox. 1: Aspiration hazard – Category 1	
Aquatic Chronic 3: Hazardous to the aquatic environment - long-term aquatic hazard – Category 3	
* Data compared to the previous version altered.	
······································	