
according to 1907/2006/EC, Article 31



Version number 2 (replaces version 1)



SECTION 1: Identification of the substance/mixture and of the company/undertaking

· 1.1 Product identifier

• Trade name: 4CR 5170 Karosseriedichtmasse

- 1.2 Relevant identified uses of the substance or mixture and uses advised against No further relevant information available.
- Application of the substance / the mixture Filler and surfacer

1.3 Details of the supplier of the safety data sheet
Manufacturer/Supplier:
4CR International GmbH & Co. KG
Donnerstrasse 10b
22763 Hamburg
Tel.: +49 (0) 40 69 60 99 30
E-Mail: Info@4CR.com
www.4CR.com
1.4 Emergency telephone number: +49(0)700 24112112 (CRM)

SECTION 2: Hazards identification

· 2.1 Classification of the substance or mixture · Classification according to Regulation (EC) No 1272/2008

flame

Flam. Liq. 3 H226 Flammable liquid and vapour.



STOT RE 2 H373 May cause damage to organs through prolonged or repeated exposure.



Skin Irrit. 2 H315 Causes skin irritation.

Eye Irrit. 2 H319 Causes serious eye irritation.

STOT SE 3 H335 May cause respiratory irritation.

· 2.2 Label elements

· Labelling according to Regulation (EC) No 1272/2008

The product is classified and labelled according to the GB CLP regulation. • *Hazard pictograms*



· Signal word Warning

Hazard-determining components of labelling: Xylene
Hazard statements
H226 Flammable liquid and vapour.
H315 Causes skin irritation.
H319 Causes serious eve irritation.

H335 May cause respiratory irritation.

(Contd. on page 2)

GB

Revision: 02.05.2023

Printing date 02.05.2023

Version number 2 (replaces version 1)

Trade name: 4CR 5170 Karosseriedichtmasse

| | (Contd. of page 1) |
|----------------------|--|
| H373 May cause a | lamage to organs through prolonged or repeated exposure. |
| · Precautionary stat | tements |
| P101 | If medical advice is needed, have product container or label at hand. |
| P102 | Keep out of reach of children. |
| P103 | Read carefully and follow all instructions. |
| P210 | Keep away from heat, hot surfaces, sparks, open flames and other ignition sources. No smoking. |
| P260 | Do not breathe dust/fume/gas/mist/vapours/spray. |
| P280 | <i>Wear protective gloves/protective clothing/eye protection/face protection/hearing protection.</i> |
| P303+P361+P35 | ³ <i>IF ON SKIN (or hair): Take off immediately all contaminated clothing. Rinse skin with water [or shower].</i> |
| P305+P351+P338 | 8 IF IN EYES: Rinse cautiously with water for several minutes. Remove contact lenses, if present and easy to do. Continue rinsing. |
| P501 | Dispose of contents/container in accordance with local/regional/national/international regulations. |
| · 2.3 Other hazards | |
| · Results of PBT an | d vPvB assessment |
| · PBT: Not applical | ble. |
| · vPvB: Not applica | ble. |

SECTION 3: Composition/information on ingredients

· 3.2 Mixtures

• Description: Mixture of substances listed below with nonhazardous additions.

| · Dangerous components: | | |
|---|--|----------|
| CAS: 1330-20-7 EINECS: 215-535-7 Reg.nr.: 01-2119488216-32 | Xylene Flam. Liq. 3, H226; STOT RE 2, H373; Asp. Tox. 1, H304; Acute Tox. 4, H312; Acute Tox. 4, H332; Skin Irrit. 2, H315; Eye Irrit. 2, H319; STOT SE 3, H335 | 25-50% |
| CAS: 100-41-4 EINECS: 202-849-4 Reg.nr.: 01-2119489370-35 | Ethylbenzene Flam. Liq. 2, H225; STOT RE 2, H373; Asp. Tox. 1, H304; Acute Tox. 4, H332; Skin Irrit. 2, H315; Eye Irrit. 2, H319; Aquatic Chronic 3, H412 | 2.5-<10% |
| Additional information: For the wording of the listed hazard phrases refer to section 16. | | |

Additional information: For the wording of the listed hazard phrases refer to section 16.

SECTION 4: First aid measures

• 4.1 Description of first aid measures

• General information: Immediately remove any clothing soiled by the product.

• After inhalation: Supply fresh air; consult doctor in case of complaints.

• After skin contact: Immediately rinse with water.

• After eye contact:

Rinse opened eye for several minutes under running water. If symptoms persist, consult a doctor.

· After swallowing: If symptoms persist consult doctor.

• 4.2 Most important symptoms and effects, both acute and delayed No further relevant information available.


• 4.3 Indication of any immediate medical attention and special treatment needed

No further relevant information available.

(Contd. on page 3)

GB

according to 1907/2006/EC, Article 31



Printing date 02.05.2023

Version number 2 (replaces version 1)

Trade name: 4CR 5170 Karosseriedichtmasse

(Contd. of page 2)

SECTION 5: Firefighting measures

- · 5.1 Extinguishing media
- · Suitable extinguishing agents:

CO2, powder or water spray. Fight larger fires with water spray or alcohol resistant foam.

- For safety reasons unsuitable extinguishing agents: Water with full jet
- 5.2 Special hazards arising from the substance or mixture
- During heating or in case of fire poisonous gases are produced.
- 5.3 Advice for firefighters
- · Protective equipment: Mouth respiratory protective device.

SECTION 6: Accidental release measures

• 6.1 Personal precautions, protective equipment and emergency procedures Mount respiratory protective device.

Wear protective equipment. Keep unprotected persons away.

- 6.2 Environmental precautions: Do not allow to enter sewers/ surface or ground water.
- 6.3 Methods and material for containment and cleaning up: Absorb with liquid-binding material (sand, diatomite, acid binders, universal binders, sawdust). Dispose contaminated material as waste according to section 13. Ensure adequate ventilation.
- **6.4 Reference to other sections** See Section 7 for information on safe handling. See Section 8 for information on personal protection equipment. See Section 13 for disposal information.

SECTION 7: Handling and storage

• 7.1 Precautions for safe handling Ensure good ventilation/exhaustion at the workplace. Prevent formation of aerosols.

• Information about fire - and explosion protection: Keep ignition sources away - Do not smoke. Protect against electrostatic charges.

Keep respiratory protective device available.

- · 7.2 Conditions for safe storage, including any incompatibilities
- Storage:
- Requirements to be met by storerooms and receptacles: No special requirements.
- · Information about storage in one common storage facility: Store away from foodstuffs.
- Further information about storage conditions: Keep container tightly sealed.

• Storage class: 3

• 7.3 Specific end use(s) No further relevant information available.

SECTION 8: Exposure controls/personal protection

· 8.1 Control parameters

· Ingredients with limit values that require monitoring at the workplace:

1330-20-7 Xylene

WEL Short-term value: 441 mg/m³, 100 ppm Long-term value: 220 mg/m³, 50 ppm

Sk; BMGV

(Contd. on page 4)

according to 1907/2006/EC, Article 31



(Contd. of page 3)

Printing date 02.05.2023

Version number 2 (replaces version 1)

Trade name: 4CR 5170 Karosseriedichtmasse

100-41-4 Ethylbenzene

WEL Short-term value: 552 mg/m³, 125 ppm Long-term value: 441 mg/m³, 100 ppm Sk

· Ingredients with biological limit values:

1330-20-7 Xylene

BMGV 650 mmol/mol creatinine Medium: urine Sampling time: post shift

Parameter: methyl hippuric acid

• Additional information: The lists valid during the making were used as basis.

· 8.2 Exposure controls

- Appropriate engineering controls No further data; see section 7.
- · Individual protection measures, such as personal protective equipment
- General protective and hygienic measures:

Keep away from foodstuffs, beverages and feed.

- Immediately remove all soiled and contaminated clothing
- Wash hands before breaks and at the end of work.
- Store protective clothing separately.
- Avoid contact with the eyes.
- Avoid contact with the eyes and skin.

• Respiratory protection:



In case of brief exposure or low pollution use respiratory filter device. In case of intensive or longer exposure use self-contained respiratory protective device.

· Hand protection

Due to missing tests no recommendation to the glove material can be given for the product/ the preparation/ the chemical mixture.

Selection of the glove material on consideration of the penetration times, rates of diffusion and the degradation



Protective gloves (EN 374)

The glove material has to be impermeable and resistant to the product/ the substance/ the preparation. • *Material of gloves*

The selection of the suitable gloves does not only depend on the material, but also on further marks of quality and varies from manufacturer to manufacturer. As the product is a preparation of several substances, the resistance of the glove material can not be calculated in advance and has therefore to be checked prior to the application.

· Breakthrough time of glove material

The exact break trough time has to be found out by the manufacturer of the protective gloves and has to be observed.

Eye/face protection



Tightly sealed goggles

(Contd. on page 5)

according to 1907/2006/EC, Article 31



(Contd. of page 4)

Printing date 02.05.2023

Version number 2 (replaces version 1)

Trade name: 4CR 5170 Karosseriedichtmasse

SECTION 9: Physical and chemical properties • 9.1 Information on basic physical and chemical properties · General Information · Physical state Fluid · Colour: According to product specification · Odour: Characteristic · Odour threshold: Not determined. • *Melting point/freezing point:* Undetermined. · Boiling point or initial boiling point and boiling 136 °C range · Flammabilitv Flammable. · Lower and upper explosion limit · Lower: 1.1 Vol % · Upper: 7 Vol % · Flash point: 23 °C (DIN 53213) • Auto-ignition temperature: >300 °C (DIN 51794) · Decomposition temperature: Not determined. · pH Not determined. · Viscosity: · Kinematic viscosity at 20 °C >60 s (DIN 53211/4) · Dynamic: Not determined. · Solubility · water: Not miscible or difficult to mix. · Partition coefficient n-octanol/water (log value) Not determined. · Vapour pressure at 20 °C: 9.5 hPa Density and/or relative density · Density at 20 °C: ~1.307 g/cm3 (DIN 53217) · Relative density Not determined. · Vapour density Not determined. • 9.2 Other information · Appearance: · Form: Pastv · Important information on protection of health and environment, and on safety. · Ignition temperature: Product is not selfigniting. Product is not explosive. However, formation of · Explosive properties: explosive air/vapour mixtures are possible. · Solvent content: 31.94 % · VOC (EC) 68.0 % · Solids content (weight-%): · Change in condition · Evaporation rate Not determined. · Information with regard to physical hazard classes · Explosives Void · Flammable gases Void · Aerosols Void · Oxidising gases Void · Gases under pressure Void · Flammable liquids Flammable liquid and vapour. · Flammable solids Void · Self-reactive substances and mixtures Void · Pyrophoric liquids Void · Pyrophoric solids Void

(Contd. on page 6)

GB

A Revision: 02.05.2023

Printing date 02.05.2023

Version number 2 (replaces version 1)

Trade name: 4CR 5170 Karosseriedichtmasse

| | | (Contd. of page 5) |
|---|------|--------------------|
| · Self-heating substances and mixtures | Void | |
| · Substances and mixtures, which emit flamm | able | |
| gases in contact with water | Void | |
| · Oxidising liquids | Void | |
| • Oxidising solids | Void | |
| · Organic peroxides | Void | |
| · Corrosive to metals | Void | |
| · Desensitised explosives | Void | |

SECTION 10: Stability and reactivity

· 10.1 Reactivity No further relevant information available.

· 10.2 Chemical stability

- Thermal decomposition / conditions to be avoided: No decomposition if used according to specifications.
- 10.3 Possibility of hazardous reactions No dangerous reactions known.
- 10.4 Conditions to avoid No further relevant information available.
- 10.5 Incompatible materials: No further relevant information available.
- 10.6 Hazardous decomposition products: Carbon monoxide

SECTION 11: Toxicological information

- · 11.1 Information on hazard classes as defined in Regulation (EC) No 1272/2008
- Acute toxicity Based on available data, the classification criteria are not met.

· LD/LC50 values relevant for classification:

1330-20-7 Xylene

| Oral | LD50 | 5,251 mg/kg (rat) |
|------------|----------|-----------------------|
| | LD50 | >5,000 mg/kg (rabbit) |
| Inhalative | LC50/4 h | 29 mg/l (rat) |

· Skin corrosion/irritation Causes skin irritation.

· Serious eye damage/irritation Causes serious eye irritation.

· STOT-single exposure May cause respiratory irritation.

· STOT-repeated exposure May cause damage to organs through prolonged or repeated exposure.

SECTION 12: Ecological information

- · 12.1 Toxicity
- Aquatic toxicity: No further relevant information available.
- · 12.2 Persistence and degradability No further relevant information available.
- 12.3 Bioaccumulative potential No further relevant information available.
- 12.4 Mobility in soil No further relevant information available.
- 12.5 Results of PBT and vPvB assessment
- **PBT:** Not applicable.
- **vPvB:** Not applicable.

• 12.6 Endocrine disrupting properties For information on endocrine disrupting properties see section 11.

- · 12.7 Other adverse effects
- Additional ecological information:
- · General notes:
- Water hazard class 2 (German Regulation) : hazardous for water

Do not allow product to reach ground water, water course or sewage system.

(Contd. on page 7)

GB



Printing date 02.05.2023

Version number 2 (replaces version 1)

Trade name: 4CR 5170 Karosseriedichtmasse

Danger to drinking water if even small quantities leak into the ground.

(Contd. of page 6)

SECTION 13: Disposal considerations

• 13.1 Waste treatment methods

· Recommendation

Must not be disposed together with household garbage. Do not allow product to reach sewage system.

- · Uncleaned packaging:
- Recommendation: Disposal must be made according to official regulations.

| 14.1 UN number or ID number ADR, IMDG, IATA | UN1263 | |
|---|---|---------------|
| 14.2 UN proper shipping name ADR IMDG, IATA | UN1263 PAINT PAINT | |
| 14.3 Transport hazard class(es) | | |
| ADR | | |
| Class Label | 3 (F1) Flammable liquids. 3 | |
| IMDG, IATA | 3 Flammable liquids. | |
| Label | 3 | |
| 14.4 Packing group ADR, IMDG, IATA | III | |
| 14.5 Environmental hazards: Marine pollutant: | No | |
| 14.6 Special precautions for user Hazard identification number (Kemler code): EMS Number: Stowage Category | Warning: Flammable liquids. 30 F-E, <u>S-E</u> A | |
| 14.7 Maritime transport in bulk according to IM instruments | 10 Not applicable. | |
| Transport/Additional information: | | |
| ADR Limited quantities (LQ) Transport category Tunnel restriction code | 5L 3 D/E | |
| | | (Contd. on pa |

according to 1907/2006/EC, Article 31



Printing date 02.05.2023

Version number 2 (replaces version 1)

Trade name: 4CR 5170 Karosseriedichtmasse

| | (Co | ontd. of page 7) |
|---|---------------------------------|------------------|
| · Remarks: | ≤ 450 l: 2.2.3.1.5 ADR | |
| IMDG Limited quantities (LQ) Remarks: | 5L ≤ 30 l: 2.2.3.5 IMDG-Code | |
| · UN "Model Regulation": | UN 1263 PAINT, 3, III | |

SECTION 15: Regulatory information

15.1 Safety, health and environmental regulations/legislation specific for the substance or mixture

- · Directive 2012/18/EU
- · Named dangerous substances ANNEX I None of the ingredients is listed.
- · Seveso category P5c FLAMMABLE LIQUIDS
- Qualifying quantity (tonnes) for the application of lower-tier requirements 5,000 t
- Qualifying quantity (tonnes) for the application of upper-tier requirements 50,000 t

· National regulations:

• Additional classification according to Decree on Hazardous Materials, Annex II:

| Class | Share in % |
|-------|------------|
| NK | 25-50 |
| | |

• 15.2 Chemical safety assessment: A Chemical Safety Assessment has not been carried out.

SECTION 16: Other information

This information is based on our present knowledge. However, this shall not constitute a guarantee for any specific product features and shall not establish a legally valid contractual relationship.

· Relevant phrases

H225 Highly flammable liquid and vapour.

H226 Flammable liquid and vapour.

- H304 May be fatal if swallowed and enters airways.
- H312 Harmful in contact with skin.

H315 Causes skin irritation.

H319 Causes serious eye irritation.

H332 Harmful if inhaled.

H335 May cause respiratory irritation.

H373 May cause damage to organs through prolonged or repeated exposure.

H412 Harmful to aquatic life with long lasting effects.

· Classification according to Regulation (EC) No 1272/2008

The classification of the mixture is generally based on the calculation method using substance data according to Regulation (EC) No 1272/2008.

· Abbreviations and acronyms: RID: Règlement international concernant le transport des marchandises dangereuses par chemin de fer (Regulations Concerning the

International Transport of Dangerous Goods by Rail) IATA-DGR: Dangerous Goods Regulations by the "International Air Transport Association" (IATA)

ICAO: International Civil Aviation Organisation

ICAO-TI: Technical Instructions by the "International Civil Aviation Organisation" (ICAO)

ADR: Accord relatif au transport international des marchandises dangereuses par route (European Agreement Concerning the International Carriage of Dangerous Goods by Road)

- IMDG: International Maritime Code for Dangerous Goods IATA: International Air Transport Association
- GHS: Globally Harmonised System of Classification and Labelling of Chemicals

EINECS: European Inventory of Existing Commercial Chemical Substances

- ELINCS: European List of Notified Chemical Substances
- CAS: Chemical Abstracts Service (division of the American Chemical Society)

VOC: Volatile Organic Compounds (USA, EU)

LC50: Lethal concentration, 50 percent

(Contd. on page 9)



(Contd. of page 8)

GE

Printing date 02.05.2023

Version number 2 (replaces version 1)

Trade name: 4CR 5170 Karosseriedichtmasse

LD50: Lethal dose, 50 percent PBT: Persistent, Bioaccumulative and Toxic vPvB: very Persistent and very Bioaccumulative Flam. Liq. 2: Flammable liquids – Category 2 Flam. Liq. 3: Flammable liquids – Category 3 Acute Tox. 4: Acute toxicity – Category 4 Skin Corrosion/irritation – Category 2 Eye Irrit. 2: Skin corrosion/irritation – Category 2 STOT SE 3: Specific target organ toxicity (single exposure) – Category 3 STOT RE 2: Specific target organ toxicity (repeated exposure) – Category 2 Asp. Tox. 1: Aspiration hazard - Category 1 Aquatic Chronic 3: Hazardous to the aquatic environment - long-term aquatic hazard - Category 3 • * Data compared to the previous version altered.