according to 1907/2006/EC, Article 31



Printing date 03.05.2023

Version number 53 (replaces version 52)

SECTION 1: Identification of the substance/mixture and of the company/undertaking

· 1.1 Product identifier · Trade name: 4CR 7441 2K Prefill Spray · 1.2 Relevant identified uses of the substance or mixture and uses advised against *No further relevant information available.* · Application of the substance / the mixture Color spray · 1.3 Details of the supplier of the safety data sheet · Manufacturer/Supplier: 4CR International GmbH & Co. KG Donnerstrasse 10b 22763 Hamburg Tel.: +49 (0) 40 69 60 99 30 E-Mail: Info@4CR.com www.4CR.com • 1.4 Emergency telephone number: +49(0)700 24112112 (CRM) **SECTION 2: Hazards identification** · 2.1 Classification of the substance or mixture · Classification according to Regulation (EC) No 1272/2008 flame H222-H229 Extremely flammable aerosol. Pressurised container: May burst if heated. Aerosol 1 Acute Tox. 4 H332 Harmful if inhaled. Eve Irrit. 2 H319 Causes serious eye irritation. Skin Sens. 1 H317 May cause an allergic skin reaction. STOT SE 3 H336 May cause drowsiness or dizziness. · 2.2 Label elements · Labelling according to Regulation (EC) No 1272/2008 The product is classified and labelled according to the GB CLP regulation. · Hazard pictograms GHS02 GHS07 · Signal word Danger · Hazard-determining components of labelling: Hexamethylene diisocyanate, oligomers acetone n-Butvl acetate · Hazard statements H222-H229 Extremely flammable aerosol. Pressurised container: May burst if heated. H332 Harmful if inhaled. H319 Causes serious eye irritation. H317 May cause an allergic skin reaction.

H336 May cause drowsiness or dizziness.

(Contd. on page 2)



Printing date 03.05.2023

Version number 53 (replaces version 52)

Trade name: 4CR 7441 2K Prefill Spray

	(Contd. of page 1)
· Precautionary stat	ements
P101	If medical advice is needed, have product container or label at hand.
P102	Keep out of reach of children.
P103	Read carefully and follow all instructions.
P210	Keep away from heat, hot surfaces, sparks, open flames and other ignition sources. No smoking.
P211	Do not spray on an open flame or other ignition source.
P251	Do not pierce or burn, even after use.
P305+P351+P338	F IN EYES: Rinse cautiously with water for several minutes. Remove contact lenses, if present and easy to do. Continue rinsing.
P410+P412	Protect from sunlight. Do not expose to temperatures exceeding 50 °C/122 °F.
P501	Dispose of contents/container in accordance with local/regional/national/international regulations.
· Additional inform	ation:
	isocyanates. May produce an allergic reaction.
Restricted to profe	
	e mixtures possible without sufficient ventilation.
· 2.3 Other hazards	
· Results of PBT an	d vPvB assessment
· PBT: Not applicat	ole.

· vPvB: Not applicable.

SECTION 3: Composition/information on ingredients

· 3.2 Mixtures

· Description: Mixture of substances listed below with nonhazardous additions.

· Dangerous components:			
CAS: 115-10-6 EINECS: 204-065-8 Reg.nr.: 01-2119472128-37	dimethyl ether 🚸 Flam. Gas 1A, H220; Press. Gas (Liq.), H280	50-100%	
CAS: 67-64-1 EINECS: 200-662-2 Reg.nr.: 01-2119471330-49	acetone Flam. Liq. 2, H225; (1) Eye Irrit. 2, H319; STOT SE 3, H336, EUH066	25-50%	
CAS: 28182-81-2 NLP: 500-060-2 Reg.nr.: 01-2119485796-17	Hexamethylene diisocyanate, oligomers Acute Tox. 4, H332; Skin Sens. 1, H317; STOT SE 3, H335, EUH204	5-<10%	
CAS: 123-86-4 EINECS: 204-658-1 Reg.nr.: 01-2119485493-29	n-Butyl acetate	5-<10%	
• Additional information: For	the wording of the listed hazard phrases refer to section 16.	1	

SECTION 4: First aid measures

• 4.1 Description of first aid measures

- General information:
- Immediately remove any clothing soiled by the product.

Symptoms of poisoning may even occur after several hours; therefore medical observation for at least 48 hours after the accident.

In case of irregular breathing or respiratory arrest provide artificial respiration.

- · After inhalation:
- Supply fresh air and to be sure call for a doctor.


In case of unconsciousness place patient stably in side position for transportation.

· After skin contact: Immediately rinse with water.

(Contd. on page 3)

GB

according to 1907/2006/EC, Article 31



Version number 53 (replaces version 52)



Trade name: 4CR 7441 2K Prefill Spray

(Contd. of page 2)

• After eye contact:

- *Rinse opened eye for several minutes under running water. If symptoms persist, consult a doctor. After swallowing: If symptoms persist consult doctor.*
- 4.2 Most important symptoms and effects, both acute and delayed No further relevant information available.
- 4.3 Indication of any immediate medical attention and special treatment needed
- No further relevant information available.

SECTION 5: Firefighting measures

- 5.1 Extinguishing media
- · Suitable extinguishing agents:
- CO2, powder or water spray. Fight larger fires with water spray or alcohol resistant foam.
- 5.2 Special hazards arising from the substance or mixture
- In case of fire, the following can be released: Nitrogen oxides (NOx) Carbon monoxide (CO)
- Hydrogen cyanide (HCN)
- 5.3 Advice for firefighters

• Protective equipment:

Mouth respiratory protective device.

Wear self-contained respiratory protective device.

Do not inhale explosion gases or combustion gases.

SECTION 6: Accidental release measures

· 6.1 Personal precautions, protective equipment and emergency procedures

Wear protective equipment. Keep unprotected persons away.

• 6.2 Environmental precautions: Do not allow to enter sewers/ surface or ground water.

- 6.3 Methods and material for containment and cleaning up:
- Dispose contaminated material as waste according to section 13.
- Ensure adequate ventilation.

Contain and collect spillages with non-combustible absorbent materials (e.g. sand, earth, diatomaceous earth) and place in a suitable container.

Decontaminate immediately with suitable mixture (flammable):

as such usable (inflammatory!):

water	45 Vol.%
ethanol or isopropanol	50 Vol.%
ammonia solution (Density= 0.88)	5 Vol.%
- alternatively (non-flammable):	
sodium carbonate	5 Vol.%
water	95 Vol.%

Add the same decontaminant to any residues and allow to stand for several days in an non-sealed container until no further reaction occurs. Once this stage is reached, close the container and dispose of in accordance with the waste regulations (see Section 13).

• 6.4 Reference to other sections

See Section 7 for information on safe handling.

See Section 8 for information on personal protection equipment.

See Section 13 for disposal information.

SECTION 7: Handling and storage

· 7.1 Precautions for safe handling

Keep away from heat and direct sunlight.

(Contd. on page 4)

according to 1907/2006/EC, Article 31 Version number 53 (replaces version 52)



Printing date 03.05.2023

Trade name: 4CR 7441 2K Prefill Spray

	(Contd. of page 3)
Ensure good ventilation/exhaustion at the workplace. Persons with a history of asthma, allergies or chronic or recurrent respiratory of employed in processes in which this product is used under appropriate medical super Information about fire - and explosion protection: Do not spray onto a naked flame or any incandescent material. Keep ignition sources away - Do not smoke. Pressurised container: protect from sunlight and do not expose to temperatures excer lights. Do not pierce or burn, even after use.	vision.
· 7.2 Conditions for safe storage, including any incompatibilities	
 Storage: Requirements to be met by storerooms and receptacles: Observe official regulations on storing packagings with pressurised containers. Information about storage in one common storage facility: Do not store together with reducing agents, heavy-metal compounds, acids and alkalu Store away from foodstuffs. Further information about storage conditions: Do not seal receptacle gas tight. Keep container tightly sealed. Store separately from oxidising agents, strongly alkaline and strongly acidic materi water. Storage class: 2 B 7.3 Specific end use(s) No further relevant information available. 	
SECTION 8: Exposure controls/personal protection	
· 8.1 Control parameters	
Ingredients with limit values that require monitoring at the workplace:	
115-10-6 dimethyl ether	
WEL Short-term value: 958 mg/m ³ , 500 ppm Long-term value: 766 mg/m ³ , 400 ppm	
67-64-1 acetone	

WEL Short-term value: 3620 mg/m³, 1500 ppm Long-term value: 1210 mg/m³, 500 ppm

28182-81-2 Hexamethylene diisocyanate, oligomers

EBW Short-term value: 0.5 mg/m³

exposition evaluation valu TRGS 430 (EBW)

123-86-4 n-Butyl acetate

WEL Short-term value: 966 mg/m³, 200 ppm

Long-term value: 724 mg/m³, 150 ppm

• Additional information: The lists valid during the making were used as basis.

· 8.2 Exposure controls

• Appropriate engineering controls No further data; see section 7.

· Individual protection measures, such as personal protective equipment

All personal protective equipment, including respiratory protective equipment, used to control exposure to hazardous substances must be selected to meet the requirements of the COSHH Regulations.

• General protective and hygienic measures: Keep away from foodstuffs, beverages and feed. Immediately remove all soiled and contaminated clothing

Wash hands before breaks and at the end of work.

Avoid contact with the eyes.

Avoid contact with the eyes and skin.

(Contd. on page 5)

⁻ GB -

according to 1907/2006/EC, Article 31



Printing date 03.05.2023

Version number 53 (replaces version 52)

Trade name: 4CR 7441 2K Prefill Spray

(Contd. of page 4)

(Contd. on page 6)

GB

· Respiratory protection:



In case of brief exposure or low pollution use respiratory filter device. In case of intensive or longer exposure use self-contained respiratory protective device.

· Hand protection

Due to missing tests no recommendation to the glove material can be given for the product/ the preparation/ the chemical mixture.

Selection of the glove material on consideration of the penetration times, rates of diffusion and the degradation



Protective gloves (EN 374)

The glove material has to be impermeable and resistant to the product/ the substance/ the preparation. • *Material of gloves*

The selection of the suitable gloves does not only depend on the material, but also on further marks of quality and varies from manufacturer to manufacturer. As the product is a preparation of several substances, the resistance of the glove material can not be calculated in advance and has therefore to be checked prior to the application.

Breakthrough time of glove material

The exact break trough time has to be found out by the manufacturer of the protective gloves and has to be observed.

• *Eye/face protection* Safety glasses



Tightly sealed goggles

SECTION 9: Physical and chemical properties

Physical state	Aerosol
Colour:	According to product specification
Odour:	Characteristic
Odour threshold:	Not determined.
Melting point/freezing point:	Undetermined.
Boiling point or initial boiling point and	boiling
range	-24 °C
Flammability	Not applicable.
Lower and upper explosion limit	
Lower:	2.6 Vol %
Upper:	18.6 Vol %
Flash point:	<0 °C (DIN 53213)
Auto-ignition temperature:	235 °C (DIN 51794)
Decomposition temperature:	Not determined.
pH	Not determined.
Viscosity:	
Kinematic viscosity	Not determined.
Dynamic:	Not determined.



Printing date 03.05.2023

Version number 53 (replaces version 52)

Trade name: 4CR 7441 2K Prefill Spray

	(Contd. of page
Solubility	
water:	Not miscible or difficult to mix.
Partition coefficient n-octanol/water (log value)	Not determined.
Vapour pressure at 20 °C:	5,200 hPa
Density and/or relative density	
Density at 20 °C:	0.742 g/cm ³ (DIN 53217)
Relative density	Not determined.
Vapour density	Not determined.
9.2 Other information	
Appearance:	
Form:	Fluid
Important information on protection of health an environment, and on safety.	d
Ignition temperature:	Product is not selfigniting.
Explosive properties:	In use, may form flammable/explosive vapour-a mixture.
Solvent content:	
· VOC (EC)	91.60 %
Solids content (weight-%):	8.4 %
Change in condition	
Evaporation rate	Not applicable.
Information with regard to physical hazard classe	
Explosives	Void
Flammable gases	Void
Aerosols	Extremely flammable aerosol. Pressurised containe
	May burst if heated.
• Oxidising gases	Void
Gases under pressure	Void
Flammable liquids	Void
Flammable solids	Void
Self-reactive substances and mixtures	Void
Pyrophoric liquids	Void
Pyrophoric solids	Void
Self-heating substances and mixtures	Void
Substances and mixtures, which emit flammable	17 - 1
gases in contact with water	Void
Oxidising liquids	Void
Oxidising solids	Void
Organic peroxides	Void
Corrosive to metals	Void V : 1
Desensitised explosives	Void

SECTION 10: Stability and reactivity

· 10.1 Reactivity No further relevant information available.

· 10.2 Chemical stability

• Thermal decomposition / conditions to be avoided: No decomposition if used according to specifications.

- · 10.3 Possibility of hazardous reactions No dangerous reactions known.
- 10.4 Conditions to avoid No further relevant information available.
- 10.5 Incompatible materials: No further relevant information available.

· 10.6 Hazardous decomposition products:

Possible in traces.

Nitrogen oxides

Hydrogen chloride (HCl)

(Contd. on page 7)

GB

according to 1907/2006/EC, Article 31



Printing date 03.05.2023

Version number 53 (replaces version 52)

Trade name: 4CR 7441 2K Prefill Spray

Hydrogen cyanide (prussic acid) Carbon monoxide Nitrogen oxides (NOx)

SECTION 11: Toxicological information

- · 11.1 Information on hazard classes as defined in Regulation (EC) No 1272/2008
- · Acute toxicity Harmful if inhaled.
- Serious eye damage/irritation Causes serious eye irritation.
- · Respiratory or skin sensitisation

This product is a respiratory sensitiser when sprayed. COSHH requires that persons exposed are subject to appropriate health surveillance.

May cause an allergic skin reaction.

· STOT-single exposure May cause drowsiness or dizziness.

• 11.2 Information on other hazards

· Endocrine disrupting properties

None of the ingredients is listed.

SECTION 12: Ecological information

- · 12.1 Toxicity
- Aquatic toxicity: No further relevant information available.
- 12.2 Persistence and degradability No further relevant information available.
- 12.3 Bioaccumulative potential No further relevant information available.
- 12.4 Mobility in soil No further relevant information available.
- · 12.5 Results of PBT and vPvB assessment
- *PBT:* Not applicable.
- · vPvB: Not applicable.
- · 12.6 Endocrine disrupting properties
- The product does not contain substances with endocrine disrupting properties.
- · 12.7 Other adverse effects
- Additional ecological information:
- · General notes:

Water hazard class 1 (German Regulation) : slightly hazardous for water

Do not allow undiluted product or large quantities of it to reach ground water, water course or sewage system.

SECTION 13: Disposal considerations

- · 13.1 Waste treatment methods
- · Recommendation

Must not be disposed together with household garbage. Do not allow product to reach sewage system.

- · Uncleaned packaging:
- *Recommendation: Disposal must be made according to official regulations.*

SECTION 14: Transport information

· 14.1 UN number or ID number · ADR, IMDG, IATA

UN1950

(Contd. on page 8)

(Contd. of page 6)

GB




Printing date 03.05.2023

Version number 53 (replaces version 52)

Trade name: 4CR 7441 2K Prefill Spray

	(Contd. of page
14.2 UN proper shipping name	
ADR	UN1950 AEROSOLS
IMDG IATA	AEROSOLS AEROSOLS, flammable
14.3 Transport hazard class(es)	ALKOSOLS, jummuoie
ADR	
Class	2 5F Gases.
Label	2.1
IMDG, IATA	
Class	2.1 Gases.
Label	2.1
14.4 Packing group	
ADR, IMDG, IATA	Void
14.5 Environmental hazards: Marine pollutant:	No
14.6 Special precautions for user	Warning: Gases.
Hazard identification number (Kemler code):	-
EMS Number: Stowage Code	F-D,S-U SW1 Protected from sources of heat.
	SW22 For AEROSOLS with a maximum capacity of litre: Category A. For AEROSOLS with a capacity abov 1 litre: Category B. For WASTE AEROSOLS: Categor C, Clear of living quarters.
Segregation Code	SG69 For AEROSOLS with a maximum capacity of litre:
	Segregation as for class 9. Stow "separated from" class except for division 1.4.
	For AEROSOLS with a capacity above 1 litre:
	Segregation as for the appropriate subdivision of class
	For WASTE AEROSOLS:
	Segregation as for the appropriate subdivision of class .
14.7 Maritime transport in bulk according to IM instruments	<i>O</i> Not applicable.
Transport/Additional information:	11
ADR	
Limited quantities (LQ)	1L
Transport category	2
Tunnel restriction code	D
IMDG	
Limited quantities (LQ)	1L
	(Contd. on page

according to 1907/2006/EC, Article 31



Version number 53 (replaces version 52)



(Contd. of page 8)

Trade name: 4CR 7441 2K Prefill Spray

• UN "Model Regulation":

UN 1950 AEROSOLS, 2.1

SECTION 15: Regulatory information

· 15.1 Safety, health and environmental regulations/legislation specific for the substance or mixture

- · Directive 2012/18/EU
- · Named dangerous substances ANNEX I None of the ingredients is listed.
- · Seveso category P3a FLAMMABLE AEROSOLS
- Qualifying quantity (tonnes) for the application of lower-tier requirements 150 t
- Qualifying quantity (tonnes) for the application of upper-tier requirements 500 t
- · National regulations:
- Additional classification according to Decree on Hazardous Materials, Annex II:

 Class
 Share in %

 NK
 50-100

· 15.2 Chemical safety assessment: A Chemical Safety Assessment has not been carried out.

SECTION 16: Other information

This information is based on our present knowledge. However, this shall not constitute a guarantee for any specific product features and shall not establish a legally valid contractual relationship.

· Relevant phrases

- H220 Extremely flammable gas.
- H225 Highly flammable liquid and vapour.
- H226 Flammable liquid and vapour.
- H280 Contains gas under pressure; may explode if heated.
- H317 May cause an allergic skin reaction.
- H319 Causes serious eye irritation.
- H332 Harmful if inhaled.
- H335 May cause respiratory irritation.
- H336 May cause drowsiness or dizziness.

EUH066 Repeated exposure may cause skin dryness or cracking.

EUH204 Contains isocyanates. May produce an allergic reaction.

· Classification according to Regulation (EC) No 1272/2008

The classification of the mixture is generally based on the calculation method using substance data according to Regulation (EC) No 1272/2008.

· Abbreviations and acronyms:

RID: Règlement international concernant le transport des marchandises dangereuses par chemin de fer (Regulations Concerning the International Transport of Dangerous Goods by Rail)

IATA-DGR: Dangerous Goods Regulations by the "International Air Transport Association" (IATA)

ICAO: International Civil Aviation Organisation

ICAO-TI: Technical Instructions by the "International Civil Aviation Organisation" (ICAO)

ADR: Accord relatif au transport international des marchandises dangereuses par route (European Agreement Concerning the International Carriage of Dangerous Goods by Road)

- IMDG: International Maritime Code for Dangerous Goods
- IATA: International Air Transport Association

GHS: Globally Harmonised System of Classification and Labelling of Chemicals

EINECS: European Inventory of Existing Commercial Chemical Substances

ELINCS: European List of Notified Chemical Substances

- CAS: Chemical Abstracts Service (division of the American Chemical Society)
- VOC: Volatile Organic Compounds (USA, EU)
- PBT: Persistent, Bioaccumulative and Toxic
- vPvB: very Persistent and very Bioaccumulative Flam. Gas 1A: Flammable gases – Category 1A
- Aerosol 1: Aerosols Category 1

Press. Gas (Liq.): Gases under pressure – Liquefied gas

(Contd. on page 10)

A Revision: 03.05.2023

Printing date 03.05.2023

Version number 53 (replaces version 52)

Trade name: 4CR 7441 2K Prefill Spray

(Contd. of page 9)

Flam. Liq. 2: Flammable liquids – Category 2 Flam. Liq. 3: Flammable liquids – Category 3 Acute Tox. 4: Acute toxicity – Category 4 Eye Irrit. 2: Serious eye damage/eye irritation – Category 2 Skin Sens. 1: Skin sensitisation – Category 1 STOT SE 3: Specific target organ toxicity (single exposure) – Category 3 • * Data compared to the previous version altered.