



Art.-No.:6.7430.0400

7430

Silver Wheel Spray

Characteristics

4CR 7430 Silver Wheel Spray is a fast drying and weathering resistant special paint for wheel rims and vehicle parts. Improves the appearance and protects wheel rims fast and efficiently.

Tech Tip

- Fast drying, weathering resistant
- Abrasion resistant, good surface hardness

Application

Substrate:

Steel rims and other similar metal surfaces, if necessary prime using 4CR 7405 in order to improve the adhesion and the protection against corrosion.

Pretreatment / Cleansing:

Pre-cleansing with 4CR silicone remover.

Processing conditions:

From +10°C and up to 80% relative air humidity.

All substrates must be clean, dry and free from grease. Shake can vigorously for approx. 3 minutes prior to use. Spraying distance approx. 20 - 30 cm. Apply several thin layers, with a flash-off period of approx. 3 - 5 minutes between each coating.

After use, turn can upside down and spray until the valve is clean, this prevents the valve from clogging up.

Technical Data

Colour	aluminium - silver
Coating Procedure	Please read the directions for use.
Dust-dry	after approx. 5 - 10 Min.
Set to touch	after approx. 20 - 30 Min.

Storage and Transportation

In tightly closed original containers at least 2 years shelf life.