Art.-No.:6.7460.0400

7460

2K Fade-out-thinner

Characteristics

4CR 2K Fade-out-thinner is a special solvent-based mixture for the dissolution of spray-dust on spot-repairs or blending work. The transition zone can be easily polished to achieve a brilliant shine.

V.O.C. Value

EC limiting value for the product (cat. B/e): 840 g/l (2007)
This product contains max. 840 g/l VOC [7.01 lbs/gal]

Tech Tip

- Ready for use.
- Apply directly onto the still wet film of paint in several thin layers.
- Excellent levelling qualities for blending work.

Application

Substrate: Can be applied on all customary 2K-fillers, 2K-basecoats and 2K-clearcoats.

Processing conditions from +10°C and up to 80% relative air humidity.

All substrates must be clean, dry and free from grease. Shake can vigorously for approx. 3 mins. prior to use. Spraying distance approx. 30 - 40 cm. Apply several thin layers, with a flash-off period of approx. 3 - 5 Minuten between each coating. After use, turn can upside down and spray until the valve is clean, this prevents the valve from clogging up.

Technical Data

Colour / Grade of Gloss	colourless
Content	400 ml

This data sheet is for information purpose only. To our knowledge the data provided complies with the latest standard and is based on years of experience in the manufacturing of our products.

...the professional choice.