Art.-No.: 6.8820.0250

8820

8820 C-GLAZE

Attributes

8820 C-GLAZE Sealant contains a high silicate sealant to protect coated and uncoated paint surfaces. 8820 C-GLAZE gives an outstanding gloss and exceptional beading behavior, combined with a silky surface feel. 8820 C-GLAZE works for months with just one job and also protects the painted surfaces from water spots to a degree.



V.O.C.

0 gr / Liter

Tech Tip

8820 C-GLAZE can be applied to existing 8830 C-PROTECT NANO coatings, the specially formulated composition that bonds with the surface and significantly extends the life of the coating. After treatment with 8820 C-GLAZE, the surfaces are in a condition just as recently coated.

Application

Apply 2-3 sprays 8820 C-GLAZE with a clean microfibre cloth on the surface until the surface is streak-free and high-gloss.
Also possible to spray directly on the surface and then distribute with cloth.
8820 C-GLAZE was developed, tested and produced in Germany.

Storage

This product is not classified as dangerous for transport. The supplier did not perform a chemical safety assessment for the substance or mixture.
At storage temperatures preferably between 15 and 25 ° C, original containers can be stored for 24 months.

This data sheet is for information! The information to the best of our knowledge is state of the art and based on many years of experience in the manufacture of our products.